

AD-A130 012


A NONSIMILAR SOLUTION FOR BLAST WAVES DRIVEN BY AN
ASYMPTOTIC PISTON EXPA. (U) ARMY ARMAMENT RESEARCH AND
DEVELOPMENT COMMAND ABERDEEN PROVI. M L BUNDY. JUN 83
ARBRL-TR-02497 SBI-AD-F300 272


1/1

UNCLASSIFIED

F/G 19/4

NL





MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS 1963-A

ADA130012

(12)

A7-F3002

AD

TECHNICAL REPORT ARBRL-TR-02497

A NONSIMILAR SOLUTION FOR BLAST WAVES
DRIVEN BY AN ASYMPTOTIC
PISTON EXPANSION

Mark L. Bundy

June 1983

DTA
ELECT
JUN 27 1983

g H



US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND
BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND

Approved for public release; distribution unlimited.

DTIC FILE COPY

83 06 27 034

Destroy this report when it is no longer needed.
Do not return it to the originator.

Additional copies of this report may be obtained
from the National Technical Information Service,
U. S. Department of Commerce, Springfield, Virginia
22161.

The findings in this report are not to be construed as
an official Department of the Army position, unless
so designated by other authorized documents.

*The use of trade names or manufacturers' names in this report
does not constitute endorsement of any commercial product.*

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER TECHNICAL REPORT ARBRL-TR-02497	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) A NONSIMILAR SOLUTION FOR BLAST WAVES DRIVEN BY AN ASYMPTOTIC PISTON EXPANSION	5. TYPE OF REPORT & PERIOD COVERED Final	
	6. PERFORMING ORG. REPORT NUMBER	
7. AUTHOR(s) M. L. Bundy	8. CONTRACT OR GRANT NUMBER(s)	
9. PERFORMING ORGANIZATION NAME AND ADDRESS US Army Ballistic Research Laboratory ATTN: DRDAR-BLL Aberdeen Proving Ground, MD 21005	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS RDT&E 1L161102AH43	
11. CONTROLLING OFFICE NAME AND ADDRESS US Army Armament Research & Development Command US Army Ballistic Research Laboratory (DRDAR-BLA-S) Aberdeen Proving Ground, MD 21005	12. REPORT DATE June 1983	
	13. NUMBER OF PAGES 26	
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	15. SECURITY CLASS. (of this report) UNCLASSIFIED	
15a. DECLASSIFICATION/DOWNGRADING SCHEDULE		
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Analytical Blast Piston Wave Driven		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) ner An analytical technique is outlined for predicting the blast wave from a rapid but asymptotic expansion of an inner piston-like surface. The method more accurately describes real blasts compared to conventional point source models and agrees favorably with the exact method of characteristic solution for wave Mach numbers exceeding approximately 1.1. The method makes two a priori assumptions: 1) that the blast wave density can be described by a power law, and 2) that an equation exists for the motion of the driving piston. The present treatment extends the work of Bach and Lee, who assume a zero radius piston (i.e., a point source).		

TABLE OF CONTENTS

	Page
I. INTRODUCTION.	5
II. PROCEDURE	5
III. RESULTS	10
IV. CONCLUSION.	13
APPENDIX A.	19
DISTRIBUTION LIST	23

Accession For	
DTIC 0P1A1	FILE
DTIC 1/2	
Unannounced	
Justification	
By	
Distribution/	
Availability Codes	
Avail and/or	
Dist	Special
A	

I. INTRODUCTION

When the contact surface of an expanding gas moves faster than the speed of sound in the stagnant medium ahead of it, a blast wave is formed. Solutions to this type of problem are of interest in a variety of practical problems such as the rupture of pressurized vessels or the blast from high energy explosives. Ignoring chemical reactions within the blast wave, the rate at which work is done in pushing aside the gas ahead of the contact surface is the prime factor in determining which analytical model will most accurately describe the real blast wave. For instance, a self-similar point source model such as that used by Taylor¹ assumes that all the work of expansion is done initially, in an infinitesimal amount of time, and is valid only for strong blast waves (i.e., high shock Mach numbers). A more realistic self-similar model such as that used by Freeman² assumes continuous energy input to the blast wave but, except for the case of a constant wave Mach number, is also valid only in the strong blast regime. Clearly what is needed is an analytical technique which is valid for all blast wave strengths and uses the realistic assumption that the energy input exists for the finite amount of time during which the piston (contact surface) expands. Such a technique is presented here; it is nonsimilar and assumes an asymptotic energy input to the blast wave. The method is applied to the specific case of the rupturing of a sphere of compressed gas and the results compared with the numerical -- method of characteristics -- solution to the identical problem.

II. PROCEDURE

Self-similar solutions assume that the shock normalized blast wave variables do not have explicit time dependence. Though this assumption may be useful when the wave is strong, it must be inaccurate for the entire blast wave history. For example, the minimum in the blast wave pressure will be located at its innermost boundary when the wave is strong but moves forward as the wave overexpands. Self-similar models correctly predict the strong wave behavior but without intrinsic time dependence are unable to predict a change in the minimum location as the wave weakens. The method used here is nonsimilar and is a modification of the procedure used by Bach and Lee³ which is not used intact because of its assumption of an instantaneous point source of energy. The Bach and Lee analysis is modified here to treat the more realistic case of an asymptotic energy supply.

-
1. G. I. Taylor, "The Formation of a Blast Wave by a Very Intense Explosion, I, Theoretical Discussion," *Proceedings of the Royal Society (London), Series A*, Vol. 201, 1950, pp. 159-174.
 2. R. A. Freeman, "Variable-Energy Blast Waves," *Brit. J. Appl. Phys. (J. Phys. D)*, Ser. 2, Vol. 1, 1968, pp. 1697-1710.
 3. G. G. Bach, and J. H. S. Lee, "An Analytical Solution for Blast Waves," *AIAA Journal*, Vol. 8, No. 2, February 1970, pp. 271-275.

Convenient coordinates for a spherically symmetric blast are

$$y = r/R_s, \quad (1)$$

where R_s is the shock front radius, and

$$n = (c_0/\dot{R}_s)^2, \quad (2)$$

where c_0 is the stagnant medium sound speed, with the dot symbolizing time differentiation. Let the density, pressure, and fluid velocity within the blast wave be defined by, respectively,

$$\rho(r,t) = \rho_0 A(y,n), \quad (3)$$

$$p(r,t) = \rho_0 (\dot{R}_s)^2 B(y,n), \quad (4)$$

$$u(r,t) = \dot{R}_s C(y,n). \quad (5)$$

One of two a priori assumptions associated with this analytical technique is to assume that the density in the blast wave conforms to

$$\rho(r,t) = \rho(R_s,t) y^q, \quad (6)$$

or equivalently

$$A(y,n) = A(1,n) y^q, \quad (7)$$

where q is a function of n to be determined. Assuming (7) for A makes it possible to solve for B and C from the equations for mass and momentum conservation alone, viz.

$$(C-y)A_y + AC_y + 2CA/y = 2hnA_n, \quad (8)$$

$$(C-y)C_y + hC + B_y/A = 2hnC_n, \quad (9)$$

where

$$h = R_s \dot{R}_s / (\dot{R}_s)^2 \quad (10)$$

with the subscripts y and n indicating partial differentiation with respect to y or n accordingly. The Rankine-Hugoniot boundary relations across the shock front are, for a polytropic gas,

$$A_1 = A(1,n) = (\gamma+1)/(\gamma-1+2n), \quad (11)$$

$$B_1 = B(1,n) = (2\gamma + n(1-\gamma))/(\gamma(\gamma+1)), \quad (12)$$

$$C_1 = C(1,n) = 2(1-n)/(\gamma+1) , \quad (13)$$

where γ is the specific heat ratio in the blast wave region. Substitution of (7) for A into the continuity Equation (8) yields upon integration the following closed form expression for C:

$$C(y,n) = y(T + (C_1 - T)y^{-(q+3)} + \gamma \ln y) , \quad (14)$$

where

$$T(q,n,h) = G(q) + hH(n,q) , \quad (15)$$

$$Y(q,n,h) = hJ(n,q) , \quad (16)$$

$$G(q) = (q)/(q+3) , \quad (17)$$

$$H(n,q) = (2nA'_1)/(A_1(q+3)) + J/(q+3) , \quad (18)$$

$$J(n,q) = (2nq')/(q+3) , \quad (19)$$

with the prime signifying total differentiation with respect to n. Substitution of (14) for C and (7) for A into the momentum Equation (9) yields upon integration a similarly closed form expression for B,

$$\begin{aligned} B(y,n) = & B_1 + A_1 (2hnT' - hT - (T-1)(T+Y))(y^{q+2} - 1)/(q+2) \\ & + A_1 (2hn(C'_1 - T') - h(C_1 - T) + (T-1)(C_1 - T)(q+2) - (C_1 - T)(T+Y))(1 - 1/y) \\ & + A_1 (2hnY' - hY - Y(2T+Y-1))((\ln y - 1/(q+2))(y^{q+2}/(q+2)) + 1/(q+2)^2) \\ & + A_1 (2hn(T - C_1)q' - Y(T - C_1)(q+1))(1 - (\ln y + 1)(1/y)) \\ & + A_1 (Y^2)(2/(q+2)^3 - (\ln^2 y - (2/(q+2))(\ln y - 1/(q+2)))(y^{q+2}/(q+2)) \\ & + A_1 ((C_1 - T)^2(q+2))(1 - y^{-(q+4)})/(q+4) . \end{aligned} \quad (20)$$

The right-hand side of the closed form fluid variable expressions, (7), (14), and (20), are completely known at any given time provided the quantities $q(t)$, $h(t)$, and $n(t)$ are known at that time. The variables q , h , and n are determined by invoking global mass and energy conservation across the

blast wave region as follows. Conservation of mass within the blast wave requires that

$$\int_{R_c}^{R_s} 4\pi\rho r^2 dr = \int_{R_o}^{R_s} 4\pi\rho_o r^2 dr , \quad (21)$$

where R_o and $R_c(t)$ are the contact surface radius at time $t=0$ and time t , respectively. Figure 1 shows the blast wave region, defined between R_c and R_s , as it evolves in time. Substitution of (6) into (21) yields upon integration an algebraic equation for q :

$$q = 3A_1(1-w^{q+3})/(1-w_o^3) - 3 , \quad (22)$$

where

$$w = R_c/R_s , \quad (23)$$

$$w_o = R_o/R_s . \quad (24)$$

Using (22) for q introduces the unknown $R_c(t)$; note R_o will be given as an initial condition of the problem. To obtain $R_c(t)$ a second a priori assumption is provided (the first being (6)); viz., it is assumed in advance that an expression for $R_c(t)$ exists. The following expression for $R_c(t)$ was found useful for modeling the contact surface of propellant plumes from guns and will be used here (though the theory remains valid for any contact surface expression):

$$R_c(t) = R_\infty(1-1/\sqrt{1+t/\tau}) + R_o , \quad (25)$$

where R_∞ and τ are two constants which for the present can be assumed known.

Note that expression (25) for the contact surface radius is asymptotic in time. With $R_c(t)$ known, the expression (22) for q depends solely on n and w . The three quantities h , n , and w are all related through the time derivatives of $R_s(t)$. By definition w satisfies

$$\dot{w} = w(\dot{R}_c - w\dot{R}_o/\sqrt{n})/R_c . \quad (26)$$

Similarly, the inverse Mach number squared, n , obeys

$$\dot{n} = -2c_o h w \sqrt{n}/R_c . \quad (27)$$

Finally, an equation for h is developed from global energy conservation as follows. For a perfect gas, let the internal energy per unit mass be given by

$$e = p/(\rho(\gamma-1)) \quad . \quad (28)$$

Using (28), global energy conservation is written

$$E_s(t) = \int_{R_c(t)}^{R_s(t)} (p/(\gamma-1) + \rho u^2/2) 4\pi r^2 dr - 4\pi R_s^3 (1-w_o^3) (\rho_o c_o^2 / (3\gamma(\gamma-1))) \quad , \quad (29)$$

where $E_s(t)$ is the work input to the blast wave from the pushing action of the piston-like contact surface and is therefore given by

$$E_s(t) = \int_{R_o}^{R_s(t)} p(w) 4\pi r^2 dr \quad . \quad (30)$$

Integration and rearrangement of (29) using (30) yields for dh/dt

$$\dot{h} = \dot{n}(L-W)/V \quad , \quad (31)$$

where

$$W(\dot{h}, n, q, w) = E_s(t) / ((4\pi \rho_o c_o^2 R_s^3) (1-w_o^3)) \quad , \quad (32)$$

$$\begin{aligned} L(h, n, q, w) = & -(1-w_o^3)/(3k(k-1)) + ((1-w^2)/2)(-a_4 - (a_8/2) + b_2 - (b_5/2)) \\ & + ((1-w^3)/3)(a_1 - a_2 + a_4 + a_6 + a_8 + 2a_9 + a_{10}) + ((1-w^{-(q+1)})/(q+1))(a_{10} + b_4) \\ & - ((w^{(q+5)} \ln^2 w)/(q+5))(b_6 - (q+2)^2 a_9) + ((1-w^{(q+5)})/(q+5))(a_2 - a_6(2q+7)/(q+5) \\ & - 2a_9((2q+7)/(q+5) + (q+2)^2/(q+5)^2) + b_1 - (b_3/(q+5)) + (2b_6/(q+5)^2)) \\ & + (w^2 \ln w/2)(a_8 - b_5) - (w^{(q+5)} \ln w/(q+5))((q+2)a_6 \\ & + 2a_9((q+2)(2q+7)/(q+5) + b_3 - (2b_6/(q+5)))) \quad , \end{aligned} \quad (33)$$

$$V(h,n,q,w) = a_5((1-w^2)/2) + ((1-w^3)/3)(a_3-a_5-a_7) \\ + ((1-w^{(q+5)})/(q+5))(a_7(2q+7)/(q+5)-a_3) + ((w^{(q+5)} \ln w)/(q+5))(a_7(q+2)), \quad (34)$$

with the a_i 's, b_i 's and c_i 's defined in the appendix. The \dot{h} dependence in (32) for w can be factored out and moved to the left-hand side in (31) but is left undone here to shorten the expressions. It is convenient for numerical solution to put (22) for q into the form

$$\dot{q} = \dot{n}(((-2A_1(1-w^{(q+3)})/(\gamma-1+2n)) - A_1(q+3)(w^{(q+2)} \dot{w}/\dot{n}))/((1-w_0^3) \\ + 3w_0^3 A_1(1-w^{(q+3)})/((2hn)(1-w_0^3)^2))/((A_1 w^{(q+3)} \ln w)/(1-w_0^3) + 1/3)) \quad (35)$$

The system of four first order ordinary differential equations for q , h , n , and w (viz. (35), (31), (27), and (26)) can be solved numerically using a Runge-Kutta procedure provided initial values for q , h , n , and w are available. To obtain these it is assumed that the initial expansion of the contact surface is analogous to the initial expansion after rupture of a shock tube diaphragm. The theory for the shock tube case has a well-known analytic solution. It will thus be assumed for simplicity that the gas expands for an initial time interval Δt_0 as if it were a one-dimensional

planar problem. Values for $R_s(\Delta t_0)$, $R_c(\Delta t_0)$, $\dot{R}_s(\Delta t_0)$, and $\dot{R}_c(\Delta t_0)$ are thus obtained and used in (22), (23), (2), and (10) to provide initial values for q , w , n , and h . Having obtained the solution for $q(t)$, $h(t)$, and $n(t)$, their substitution into (7), (14), and (20) yields the blast wave density, velocity, and pressure, respectively, at that time as a function of y alone.

This treatment is fundamentally different from References 1-3 in that it is not a point blast theory. Unlike References 1-3, $R_c(t)$ and R_0 are not assumed zero. In fact, replacing $R_c(t)$ and R_0 by zero in the above expressions reduces them to their point blast counterparts in Reference 3. The present method is now demonstrated on a hypothetical test case.

III. RESULTS

Using (25) for $R_c(t)$, assume that an ideal gas, with

$$\begin{aligned} \tilde{\gamma} \text{ (specific heat)} &= 1.25, \\ \tilde{T} \text{ (temperature)} &= 2831^\circ \text{K}, \\ \tilde{v} \text{ (moles)} &= 1.63 \text{ moles}, \\ \tilde{m} \text{ (mass/mole)} &= 0.024 \text{ kg/mol}, \end{aligned} \quad (36)$$

is confined within a spherical volume, of radius

$$R_0 = 0.1 \text{ m} , \quad (37)$$

which ruptures at time $t = 0$. The solution for the ensuing blast wave is predicted using both the present analytical technique and a more exact non-isentropic method of characteristics technique. For comparison, the results are also nondimensionalized and compared with the point blast model of Bach and Lee.

For the purpose of evaluating R_∞ , used in (25), let it be assumed that the compressed gas undergoes an irreversible and adiabatic expansion against a background pressure of one atmosphere. Under these conditions, conservation of energy will lead to the following equation for the final radius

$$R_\infty = (3\tilde{v}k\tilde{T}/(4\pi\tilde{\gamma}p_0))^{(1/3)} - R_0 , \quad (38)$$

where k is the universal gas constant and p_0 is one atmosphere of pressure both in the SI system. Furthermore, to evaluate τ , in (25), use again the assumption that the initial expansion of the compressed gas in the radial direction can be approximated by a one-dimensional planar expansion in a shock tube. In which case the contact surface velocity at $t = 0$ is given by

$$\dot{R}_c(t=0) = R_\infty/(2\tau) = c_0 Z/(\gamma(1+(\gamma+1)Z/(2\gamma))^{1/2}) , \quad (39)$$

where the first equality in (39) is obtained from the time derivative of (25) at $t = 0$, and Z in the last equality must satisfy

$$Z/(\gamma(1+(\gamma+1)Z/(2\gamma))^{1/2}) = (2\tilde{c}/(c_0(\tilde{\gamma}-1)))(1-(p_0(1+Z)/\tilde{p}))^{(\tilde{\gamma}-1)/2\tilde{\gamma}} , \quad (40)$$

where

$$\tilde{p} = \tilde{v}k\tilde{T}/(4\pi R_0^3/3) , \quad (41)$$

$$\tilde{c} = (\tilde{\gamma}\tilde{p}/(\tilde{v}m/(4\pi R_0^3/3)))^{1/2} . \quad (42)$$

From (39)

$$\tau = R_\infty(\gamma(1+(\gamma+1)Z/(2\gamma))^{1/2}/(2c_0 Z)) . \quad (43)$$

Though the analysis leading to (38) and (43) is oversimplified, the expressions thus obtained were useful for the intended purpose of (25), viz., to predict the contact surface radius of the exhaust gases expelled after shot ejection from guns. In any case, the expression used for the contact surface radius is not at issue in the present treatment; it is merely assumed

a priori that such an expression exists. Obtaining (38) and (43) for use in (25) gives the appropriate $R_c(t)$ for the example under investigation. The complete results for this test case are shown in Figures 2-4. Figure 2 is a composite of the time variation of: (a) the exponent q used in (6) for the power law form of the density; (b) the Mach number of the shock front, $M = n^{-1/2}$; and (c) the fraction of energy input at time t to the total energy input at time $t = \infty$. (The scale of time is chosen to show the most dramatic change in the variables, which in this problem is from $t = 0$ to $t = 4500 \mu\text{sec}$.) Figure 2(c) shows that the energy input to the blast wave is indeed asymptotic with time as opposed to the instantaneous input characteristic of point blast theories. A comparison between the results predicted by the point blast theory of Bach and Lee and the present treatment is summarized in non-dimensional format in Figure 3. Perhaps surprising in view of their inherent differences is the closeness in the curves of Figure 3(a) for the shock trajectory R_s/R_e vs n , where

$$R_e = (E_{\text{total}} / (\rho_0 c^2 4\pi))^{1/3} \quad (44)$$

It appears from this plot that approximating a timed release of energy E_{total} by an instantaneous release of E_{total} has essentially no effect on the predicted shock trajectory. On the other hand, Figures 3(b) - 3(d) show that there are differences in the predicted profiles of the other fluid variables. (The subscript 1 refers to the value at the shock.) Most noticeable of these is the difference in the inner boundary of the blast wave which is $r = 0$ for the point blast model and $r = R_c(t)$ for the piston blast model. In Figures 3(c) and 3(d), the piston blast solution falls within the limits predicted by the point blast solution. But Figure 3(b) shows a significant difference between the piston and point blast solutions. In the latter case, the fluid velocity has a substantial negative phase while in the former case the velocity is only beginning to show a region of reversed flow. In order that Figure 3 may be taken with confidence to illustrate the inherent limitations in the point blast approximation, a comparison is made between the piston solution used in Figure 3 and a more exact numerical solution. To serve this purpose, a nonisentropic, numerical method of characteristic (M.O.C.) solution was obtained for this problem. A comparison between solutions is shown at four different times in Figure 4. The particular times chosen illustrate collectively the full range of variable profiles. The time spanned in Figure 4 correlates with the time scale in Figure 2. In addition, the $n = 0.82$ solution of Figure 3 corresponds to the analytical solution shown in Figure 4(c). Shown at each time in Figure 4 are four subplots. The time of Figure 4(a), for example, is indicated by the dashed horizontal line in the top subplot. Following this dashed line across to the piston and shock curves and then down to the horizontal axis (distance axis) defines the blast wave region at this time. The blast wave region is marked through each of the lower subplots by vertical dashed lines. Each of the lower subplots - pressure, density, and velocity - shows the profile of the corresponding fluid variable as it changes from the piston to the shock. The analytical solution shows good agreement in all four subplots when the blast is strong, Figures 4(a) and 4(b). The favorable comparison has diminished, however, at the time

of Figure 4(c). Figure 4(d) shows that the disagreement which began in the density variable, cf. Figure 4(c), now appears in all the fluid variables except the shock trajectory, which as noted in Figure 3 is a relatively insensitive quantity.

IV. CONCLUSION

The analytical point blast solution of Bach and Lee, which is based on a power law form for the density, is extended here to describe the more realistic case of blast waves driven by an asymptotic piston-like motion of an expanding inner gas. For the same total blast energy, it was found that the piston and point blast solutions predict virtually the same shock trajectory. However, the point blast model predicts overexpansion in the velocity profile significantly earlier than the piston blast solution. The analytical piston blast solution compared well with the more exact M.O.C. solution at Mach numbers greater than approximately 1.1. Theoretical disagreement appears first in the density profile but, as the wave weakens, is observed in all the fluid variables, with the exception of the shock trajectory. Thus, the analytic technique presented here for blast waves driven by a finite piston expansion supersedes its point blast predecessor, Reference 3, by giving a more accurate description of real blasts. The technique is also a viable alternative to numerical solutions provided the Mach number of the blast wave remains above approximately 1.1.




Fig. 1 Blast wave pressure contours at two widely separated times, where $R_c(t)$ is the contact surface radius, $R_s(t)$ is the shock front radius, R_0 is the initial (preburst) sphere radius, and P_0 is the ambient background pressure




Fig. 2 Time variation of: a) the density's power law exponent q , b) the shock Mach number, and c) the fractional energy input to the blast wave.




Fig. 3 Present piston blast theory (—) vs point blast theory of Bach and Lee (- · -) for: a) shock trajectory vs shock strength; and b) - d), variation of velocity, density, and pressure within the blast wave.




Fig. 4 Analytical (—) and numerical (ooo) predictions for the velocity(u), density(ρ), pressure(p), and shock trajectory of the blast wave for the times: a) $22.5 \mu\text{sec}$, $\text{Mach}(M)=4.0$; b) $89 \mu\text{sec}$, $M=2.6$; c) $1552 \mu\text{sec}$, $M=1.1$; and d) $4050 \mu\text{sec}$, $M=1.02$.

APPENDIX A

APPENDIX A

The a_i 's, b_i 's and c_i 's used in (32) - (34) are as follows:

$$a_1 = B_1 / (n(\gamma - 1))$$

$$a_2 = A_1 ((2hn)(G' + hH') - hT + (1 - T)(T + Y)) / (n(q + 2)(\gamma - 1))$$

$$a_3 = A_1 2hH / ((q + 2)(\gamma - 1))$$

$$a_4 = A_1 ((2hn)(C_1' - G' - hH') + h(T - C_1) + (T - 1)(C_1 - T)(q + 2) + (T - C_1)(T + Y)) / (n(\gamma - 1))$$

$$a_5 = -A_1 2hH / (\gamma - 1)$$

$$a_6 = A_1 (2h^2 n J' - hY + Y(1 - 2T - Y)) / (n(\gamma - 1)(q + 2)^2)$$

$$a_7 = A_1 2hJ / ((\gamma - 1)(q + 2)^2)$$

$$a_8 = A_1 (2hn)(T - C_1)(\dot{q}/\dot{n}) + Y(C_1 - T)(q + 1) / (n(\gamma - 1))$$

$$a_9 = A_1 Y^2 / (n(\gamma - 1)(q + 2)^3)$$

$$a_{10} = A_1 ((q + 2)(C_1 - T)^2) / (n(\gamma - 1)(q + 4))$$

$$b_1 = A_1 T^2 / 2n$$

$$b_2 = A_1 T(C_1 - T) / n$$

$$b_3 = A_1 TY / n$$

$$b_4 = -A_1 (C_1 - T)^2 / 2n$$

$$b_5 = A_1 Y(C_1 - T) / n$$

$$b_6 = A_1 Y^2 / 2n$$

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
12	Administrator Defense Technical Info Center ATTN: DTIC-DDA Cameron Station Alexandria, VA 22314	7	Commander US Army Armament Research and Development Command ATTN: DRDAR-TDS, Mr. Lindner DRDAR-TDA, Mr. Blick DRDAR-LC-F, Mr. A. Loeb DRDAR-LC, Mr. Frasier DRDAR-SC, Mr. Adams DRDAR-TDC, Dr. Gyrog DRDAR-TD, Mr. A. Moss Dover, NJ 07801
1	ODCSI, USAREUR & 7A ATTN: AEAGB-PDN(S&E) APO, NY 09403	2	Commander US Army Armament Materiel Readiness Command ATTN: DRSAR-LEP-L, Tech Lib Deputy for Life Cycle Manage- ment (Mr. Ambrosini) Rock Island, IL 61299
1	HQDA (DAMA-CSM, LTC Germann) Pentagon Washington, DC 20310	2	Director US Army ARRADCOM Benet Weapons Laboratory ATTN: DRDAR-LCB-TL DRDAR-LCB (Mr. P. Rummel) Watervliet, NY 12189
1	Commander US Army Ballistic Missile Defense Systems Command Huntsville, AL 35807	1	Commander US Army Aviation Research and Development Command ATTN: DRDAV-E 4300 Goodfellow Boulevard St. Louis, MO 63120
1	Commander US Army Materiel Development and Readiness Command ATTN: DRCMD-ST 5001 Eisenhower Avenue Alexandria, VA 22333	1	Director US Army Air Mobility Research and Development Laboratory Ames Research Center Moffett Field, CA 94035
1	Commander US Army Materiel Development and Readiness Command ATTN: DRCDL 5001 Eisenhower Avenue Alexandria, VA 22333	1	Commander US Army Communications Rsch and Development Command ATTN: DRSEL-ATDD Fort Monmouth, NJ 07703
1	Commander US Army Materiel Development and Readiness Command ATTN: DRCDE-R, Mr. Lockert 5001 Eisenhower Avenue Alexandria, VA 22333		
2	Commander US Army Armament Research and Development Command ATTN: DRDAR-TSS Dover, NJ 07801		

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Commander US Army Electronics Research and Development Command Technical Support Activity ATTN: DELSD-L Fort Monmouth, NJ 07703	1	Commander US Army Research Office ATTN: CRD-AA-EH P.O. Box 12211 Research Triangle Park NC 27709
1	Commander US Army Missile Command ATTN: DRSMI-R Redstone Arsenal, AL 35898	1	Director US Army TRADOC Systems Analysis Activity ATTN: ATAA-SL White Sands Missile Range NM 88002
1	Commander US Army Missile Command ATTN: DRSMI-YDL Redstone Arsenal, AL 35898	3	Commander Naval Air Systems Command ATTN: AIR-604 Washington, DC 20360
1	Commander US Army Missile Command ATTN: DRSMI-TLH (Ricks) Redstone Arsenal, AL 35898	2	Commander and Director David W. Taylor Naval Ship Research & Development Cntr ATTN: Lib Div, Code 522 Aerodynamic Lab Bethesda, MD 20084
1	Commander US Army Natick Research and Development Command ATTN: DRDNA-DT, Dr. D. Sieling Natick, MA 01762	3	Commander Naval Surface Weapons Center ATTN: Code 6X Mr. F. H. Maille Dr. J. Yagla Dr. G. Moore Dahlgren, VA 22448
1	Commander US Army Tank Automotive Command ATTN: DRSTA-TSL Warren, MI 48090	1	Commander Naval Surface Weapons Center ATTN: Code 730, Tech Lib Silver Spring, MD 20910
1	Commander US Army Jefferson Proving Ground ATTN: STEJP-TD-D Madison, IN 47251	1	Commander Naval Weapons Center ATTN: Code 3431, Tech Lib China Lake, CA 93555
1	Commander US Army Materials and Mechanics Research Center ATTN: DRXMR-ATL Watertown, MA 02172		
2	Commandant US Army Infantry School ATTN: ATSH-CD-CSO-OR Fort Benning, GA 31905		

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Commander Naval Research Laboratory ATTN: Tech Info Div Washington, DC 20375	1	ARO, Inc. ATTN: Tech Lib Arnold AFS, TN 37389
1	Commander Naval Ordnance Station ATTN: Code FS13A, P. Sewell Indian Head, MD 20640	1	ARO, Inc. Von Karman Gasdynamics Facility ATTN: Range K Arnold AFS, TN 37389
1	AFRPL/LKCC, C.D. Penn Edwards AFB, CA 93523	1	Battelle Memorial Institute ATTN: J. E. Backofen, Jr. 505 King Avenue Columbus, OH 43201
3	AFATL (DLDL, D.C. Daniel; Tech Lib; G. Winchenbach) Eglin AFB, FL 32542	1	General Electric Company Armaments Division ATTN: Mr. R. Whyte Lakeside Avenue Burlington, VT 05401
1	AFWL/SUL Kirtland AFB, NM 87115	1	Honeywell, Inc. ATTN: Mail Station MN 112190 (G. Stilley) 600 Second Street, North Hopkins, MN 55343
1	Director National Aeronautics and Space Administration George C. Marshall Space Flight Center ATTN: MS-I, Lib Huntsville, AL 38512	2	Sandia Laboratories ATTN: Aerodynamics Dept Org 5620, R. Maydew Albuquerque, NM 87115
1	Director Jet Propulsion Laboratory ATTN: Tech Lib 4800 Oak Grove Drive Pasadena, CA 91103	1	Guggenheim Aeronautical Lab California Institute of Tech ATTN: Tech Lib Pasadena, CA 91104
1	Director NASA Scientific & Technical Information Facility ATTN: SAK/DL P.O. Box 8757 Baltimore/Washington International Airport, MD 21240	1	Franklin Institute ATTN: Tech Lib 20th & Parkway Philadelphia, PA 19103
		1	Director Applied Physics Laboratory The John Hopkins University Johns Hopkins Road Laurel, MD 20707

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>Aberdeen Proving Ground</u>
1	Massachusetts Institute of Technology Dept of Aeronautics and Astronautics ATTN: Tech Lib 77 Massachusetts Avenue Cambridge, MA 02139	Dir, USAMSAA ATTN: DRXSY-D DRXSY-MP, H. Cohen Cdr, USATECOM ATTN: DRSTE-TO-F Mr. L. Weston
1	Ohio State University Dept of Aeronautics and Astronautical Engineering ATTN: Tech Lib Columbus, OH 43210	Cdr, USACSL, Bldg. E3516, EA ATTN: DRDAR-CLB-PA DRDAR-CLJ-L DRDAR-CLN
1	Polytechnic Institute of New York Graduate Center ATTN: Tech Lib Route 110 Farmingdale, NY 11735	Dir, USAHEL ATTN: Dr. Weisz Dir, USAMTD
1	Director Foresstal Research Center Princeton University Princeton, NJ 08540	

USER EVALUATION OF REPORT

Please take a few minutes to answer the questions below; tear out this sheet, fold as indicated, staple or tape closed, and place in the mail. Your comments will provide us with information for improving future reports.

1. BRL Report Number _____
2. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which report will be used.)

3. How, specifically, is the report being used? (Information source, design data or procedure, management procedure, source of ideas, etc.) _____

4. Has the information in this report led to any quantitative savings as far as man-hours/contract dollars saved, operating costs avoided, efficiencies achieved, etc.? If so, please elaborate.

5. General Comments (Indicate what you think should be changed to make this report and future reports of this type more responsive to your needs, more usable, improve readability, etc.) _____

6. If you would like to be contacted by the personnel who prepared this report to raise specific questions or discuss the topic, please fill in the following information.

Name: _____

Telephone Number: _____

Organization Address: _____

----- FOLD HERE -----

Director
US Army Ballistic Research Laboratory
ATTN: DRDAR-BLA-S
Aberdeen Proving Ground, MD 21005




NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE, \$300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON, DC
POSTAGE WILL BE PAID BY DEPARTMENT OF THE ARMY

Director
US Army Ballistic Research Laboratory
ATTN: DRDAR-BLA-S
Aberdeen Proving Ground, MD 21005



----- FOLD HERE -----

END

FILMED

7-83

DTIC